

Model No: CT-24BE1

Main Feature:

1. 24pcs IR LED (IR distance 20 meters when IR on)
2. CDS Auto Control in Low Lux
3. Aluminum casing ,separated dual-glasses
4. ESD protection up to 5000-volt power supply
5. Voltage: DC-12V ,9 V to 15 V can be work normally
6. Day color , black and white at night
7. OSD Menu



Specifications

| | |
|-------------------------|------------------------------------|
| Model No. | CT-24BE1 |
| CCD Sensor | 1/3 Sony CCD |
| CCTV SYSTEM | PAL |
| Number of pixels | PAL:768(H)X494(V) |
| Scanning System | 700TV Lines, 50 Field/Sec |
| Sync System | Internal Synchronization |
| Horizontal Resolution | 700 TV Lines |
| Lens | 3.6mm Lens |
| Usable illumination | 0 LUX (IR LED ON) |
| Power Current | 110mA IR LED off , 450mA IR LED On |
| S/N Ratio | ≥55 dB |
| Gamma characteristic | 0.45 |
| Video output | 1.0Vp-p, 75 ohm |
| Electronic Shutter time | Auto : 1/50~1/100,000Sec |
| Operation Temperature | -10 ~+50 RH95%Max |
| Storage Temperature | -20 ~+60 RH95%Max |
| Power supply | DC 12V±15% |
| Weight | 600g |
| Dimension | 190 x 80x 80 mm |