

## Model No: CT-90BE3

### Main Feature:

- \* 72pcs  $\phi$ 5 LED (IR distance 60 meters when IR on)
- \* CDS Auto Control in Low Lux
- \* Grey metal casing, separated dual-glasses
- \* ESD surge protection up to 5000 - volt power supply
- \* Day & Night (Automatic from color to black)
- \* Low power consumption
- \* Long life multi angle IR LED
- \* OSD Menu



### SPECIFICATION

Image sensor 1/3" Sony Effio-E CCD	AGC Auto
Resolution 700 TVL	IR LED 72 pcs 5mm IR Led 60 meter
Total Pixels (HxV) PAL: 976(H) x 582(V)	IR LED Operation On (1 Lux) / Off (3 Lux)
Scanning Frequency PAL: 15.625 KHz (H), 50Hz (V)	LED life More than 10,000 hours
Scanning System 2:1 Interlace	Power Requirement DC12V ( $\pm$ 10%)
S/N Ratio More than 52dB (AGC Off)	Power consumption IR on: 580mA, IR off: 70mA
Min. Illumination 0.8 / 0.001 LUX	Cable BNC
Sync. System Synchronization	Operation Temp -10° C ~ +50° C RH95% MAX
Electronic Shutter PAL: 1/50 sec	Storage Temp -20° C ~ +60° C RH95% MAX
Gamma Y = 0.45	Lens 2.8-12mm
Video Output 1.0 Vp-p Composite (75 $\Omega$ )	Dimension 200X80X131mm